



SK LIQUID

Fountain Solution
润版液

30036

Fount System Cleaner

Fountain Solution should be consistent at all times. If a build-up of ink, paper coatings or calcium occurs, then the pH and conductivity of the working fountain solution will start to change, leading to dampening related problems. Systems Cleaner is designed to clean and remove ink, paper coatings, mold and calcium from the press circulating system. This ensures consistent quality and longer life of the fountain solution.

Advantages:

- Cleans the entire circulation system, including hoses
- Eliminates the need to dismantle in order to clean system
- Easy to use, entire cleaning procedure takes about 45 minutes

- No hot water is required
- Helps to keep fountain solution consistent

Recommendations for use:

A normal recommended dosage is 5% per liter of water in the circulation tank. Circulate for about 45 minutes, drain dirty water. Flush and rinse with clean water. Once the circulation tank has been adequately flushed, measure out fresh fountain solution and resume printing.

Physical and chemical properties:

Appearance: Liquid

Solubility: Completely soluble in water

VOC: 92 g/l

Colour: Opaque

Boiling point: 90 C

pH concentrate: 11

Odour: Glycol ether odour

Relative density: 1.0 @ 20 C

Flash point: No flash

Packaging: 5 liters / 1 box x 20 liters

润湿系统清洗剂

润版液应始终保持顺畅。如果油墨、纸屑或钙化物淤积，就会导致润版液的pH值和传导性改变，从而影响相关浸润功能。

系统清洗剂专为排除印刷循环系统沉积的油墨、纸屑、霉菌或钙化物，以此保证了润版液的长期有效和使用寿命。

优点:

- 清洁包括软管在内的整个循环系统。
- 不需加入热水。
- 清洗系统时无需拆除。
- 使润版液顺畅。
- 方便易用，整个清洗过程只需45分钟。

使用方法:

建议在水箱内每公升水加入5-6%的用量。使循环约45分钟，排出脏水，用清水冲洗。水箱冲洗干净后，加入新的润版液，即可开始印刷。

外观: 液体

气味: 乙二醇气味

沸点: 90 C

VOC: 92 g/l

闪点: 无

颜色: 不透明

溶解性: 完全溶于水

相对密度: 20°C时1.0

pH值: 11

包装: 5 公升/桶 4桶/箱

